

SENSIT[®] P400

PERSONAL MONITOR

Environments
Rapidly Change
So Should Your
Gas Monitor
Stay Safe with
IDS



SENSIT[®] P400 will alert workers of dangerous levels of combustibles, toxic gases or oxygen

MADE IN USA

SENSIT[®] P400

MULTI GAS PERSONAL MONITOR

SENSIT[®] P400 features the Immediate Detection System (IDS); an early warning system to alert you as your environment changes.

When combustible or toxic gas levels are on the rise, the P400 will automatically alert you when the environment in your workspace starts to change. At multiple stages, customized settings stand guard to warn you as conditions worsen...**before** full alarm activation.

In Hazmat response or confined space work knowledge is safety. Stay safe with IDS.

Large, Easy to Read Display

Extremely Rugged Design

Immediate Detection System*

Extremely Fast Response

Simple Field Maintenance

Low Cost of Ownership

Many Sensor Options

Made In USA

Available Sensors

Hydrogen Sulfide (H₂S)
Hydrogen Cyanide (HCN)
Oxygen (O₂)
Carbon Monoxide (CO)
Chlorine (Cl₂)
Nitrogen Dioxide (NO₂)
Phosphine (PH₃)
Sulfur Dioxide (SO₂)
Ethylene Oxide (ETO)
Combustible Gases

P400 Standard Features

- Audible Alarm - 3 Tone
- Visual Alarm - 270° View
- Vibration Alarm
- STEL and TWA Alarms
- Compliance/Status Indicator
- Data Logging
- Easy Field Calibration
- Easy Clean Dust Pre-Filter
- Easy-Access Reusable Dust Filter
- Alkaline and/or NiMH Battery
- Limited 2-Year Warranty (Including Sensors)
- Extended Warranty Available



INDUSTRY USERS

Utilities
Maintenance
Fire Departments
Safety Inspectors
Home Inspectors
Water/Sewer Departments
Heating Contractors
Utility Contractors
Industrial Plants
Propane Marketers

APPLICATIONS

Oil & Gas Exploration
Gas Contractors
Emergency Responders
Emergency Medical Personnel
Confined Space

***Optional, Immediate Detection System (IDS) provides early warning to changes in gas concentrations.**

(Patent Pending)

*Contact Sensit Technologies for more info.



COMPLIANCE/
STATUS INDICATOR

ALARM LEDs

SENSOR AREA

SENSOR FILTER

FUNCTION BUTTONS

SOUNDER

GRAPHIC DISPLAY w/BACK LIGHT

BELT CLIP (ON BACK)

TO OPERATE:

1. Press Power
2. Wait 30 Seconds for Automatic Zeroing
3. Begin to Use

Patented



STANDARD KIT

Belt Clip
Instruction Manual
Calibration Adapter
Dust Pre-Filter
Batteries
Screwdriver
Hex Wrench

KIT OPTIONS

Carry Case Pouch
Confined-Space Entry Kit
Calibration Station
Calibration Kit
Recharger Battery Pack
Recharger Station

SENSOR SPECIFICATIONS

TYPE	RESOLUTION	RANGE	ACCURACY	RESPONSE T90 TIMES
LEL	0.1 - 2.0%	0-100	±10%	< 10 Sec
O2	0.1%	25%	±0.2% or 10%**	< 10 Sec
CO	1ppm	0-999*	±5ppm or 10%**	< 10 Sec
H2S	0.1 or 1ppm	0-100	±2ppm or 10%**	< 20 Sec
HCN	0.1ppm	0-30	±1ppm or 10%**	< 20 Sec
Cl ₂	0.1ppm	0-20	±1ppm or 10%**	< 20 Sec
NO ₂	1ppm	0-250	±2ppm or 10%**	< 20 Sec
PH ₃	0.1ppm	0-10	±1ppm or 10%**	< 20 Sec
SO ₂	0.1ppm	0-20	±1ppm or 10%**	< 20 Sec
ETO	0.1ppm	0-10	±1ppm or 10%**	< 20 Sec

** Whichever is greater

PRODUCT SPECIFICATIONS

Size:	5.2" x 3.2" x 1.7" (13.2 x 8.1 x 4.0 cm)
Weight:	12 oz. (340 g)
Operational Temp:	-4 to 122 F (-20 to 50° C)
Humidity:	10-90% RH (Non-condensing)
Power Source:	4 "AA" Alkaline or NiMH Recharger Pack
Battery Life:	24 Hr. Alkaline or 15 Hr. NiMH
Sound:	98db @ 15" (30cm)

OPTIONAL FEATURES

IDS (Immediate Detection System) Pre-Alarm Indicator

High Performance Motorized Sample Pump with Filter and 10ft. Tubing and Probe Samples up to 100ft.

Remote Sample Draw Assembly Aspirator with 10ft. Tubing and Probe

Serial Communication

Stainless Steel Clip

*CO Extended Display Option:


Detection Range: 0ppm - 1999ppm



For Class 1, Division 1, Groups A, B, C and D Hazardous locations when used with approved alkaline batteries or rechargeable battery pack.

IP65

Temp code: T4, -20° C to 50° C



Ex d ia IIC T4, Gb, IP65
-20° C to 50° C
DEMKO 12 ATEX 1102012

SENSIT P400 COMMON CONFIGURATIONS

LEL
Part # 923-00000-10

LEL, O2
Part # 923-00000-20

LEL, O2, CO
Part # 923-00000-30

LEL, O2, CO, H2S
Part # 923-00000-40

LEL, O2, H2S
Part # 923-00000-27

LEL, O2, CO, HCN
Part # 923-00000-33

LEL, O2, CO, H2S, HCN
Part # 923-00000-53

LEL, O2, H2S, CO, SO2
Part # 923-00000-55

Contact Sensit for use with HCN, CL2, NO, SO2, PH3

Calibration Kits

LEL, O2, CO, H2S
Part # 881-00082

Contact Sensit for other gases.

Accessories

Pump Assembly
Part # 870-00042

PRODUCT / APPLICATION OPTIONS

SENSIT® SCAL-400 automatically charges, bump test, calibrates, downloads and saves calibration and operational data of any **SENSIT® P400 GAS MONITOR**.

SENSIT® P100

PERSONAL MONITOR

SENSIT® P100 is a single gas personal monitor designed to warn the user of hazardous gases in their working environment.



SENSIT® GOLD G2

GAS DETECTION INSTRUMENT

SENSIT® GOLD G2 is the most versatile and user-friendly SENSIT instrument available.

Displays Up To 4 Gases Simultaneously

- LEL (%Volume and PPM Optional)
- Oxygen
- Carbon Monoxide
- Hydrogen Sulfide
- Hydrogen Cyanide (Optionally)



Trak-It® IIIa

COMBUSTIBLE GAS INDICATOR

TRAK-IT® IIIa displays up to 4 gases and can be configured for combustible gas readings in PPM, LEL and/or percent volume as well as a variety of toxic sensors and oxygen.



Coming Soon: SCAL-400

For more information, visit www.gasleaksensors.com



851 Transport Drive
Valparaiso, IN 46383-8432

Phone: 888 4SENSIT
888 473 6748
219 465 2700

Fax: 219 465 2701
www.gasleaksensors.com

MADE IN USA

SENSIT Technologies
is in compliance with ISO 9001:2008



Distributed by:

